

**AVR 系列塑料面板继电器控制交流稳压器**  
**PLASTIC SURFACE PLATE VOLTAGE STABILIZER**  
**AVR SERIES/RELAY TYPE**



Model	AVR-500VA	AVR-1000VA	AVR-1500VA	AVR-2000VA	AVR-3000VA	AVR-5000VA	AVR-8000VA	AVR-10KVA		
Power	500VA	1000VA	1500VA	2000VA	3000VA	5000VA	8000VA	10KVA		
Input	Input voltage Range		140-260VAC							
	Input Frequency		50/60Hz							
Output	Output voltage		220 VAC							
	Output Precision		± 8%							
Efficiency	98%									
Phase	Single Phase									
Meter display status	Input voltage / Output voltage									
LED display status	WORKING		Green; Indicating power ON/OFF.							
	DELAYING		Yellow; During delay, this LED goes on, delay finished, goes off.							
	UNUSUAL		Red; Indicating the machine is executing protection, when protection finished, goes off.							
Environmental	Operating temperature		0~40℃							
	Storage Temperature		-15℃~45℃							
	Operating Relative Humidity		10% RH~102%RH; Non-condensing							
Physical	Machine Size(mm)		233×110 ×152	255×125 ×171	265×140 ×188	265×140 ×188	352×220 ×256	352×220 ×256	410×220 ×256	410×220 ×256
	N.W.(Kgs)		2.25	3.65	4.5	5.33	9.0	12.8	17.2	19.55