

SVR 系列经典塑料面板电子式稳压器
 CLASSIC SERIES
 SVR SERIES/RELAY TYPE



SVR-500VA



SVR-1000VA



SVR-1500VA



SVR-2000VA



SVR-3000VA



SVR-5000VA

Model		SVR-500VA	SVR-1000VA	SVR-1500VA	SVR-2000VA	SVR-3000VA	SVR-5000VA
Power		500VA	1000VA	1500VA	2000VA	3000VA	5000VA
Input	Input voltage Range	140-260VAC					
	Input Frequency	50/60Hz					
Output	Output voltage	220 VAC					
	Output Precision	± 8%					
Efficiency		98%					
Phase		Single Phase					
Meter display status		Input voltage / Output voltage					
LED display status	WORKING	Green; Indicating power ON/OFF.					
	DELAYING	Yellow; During delay, this LED goes on, delay finished, goes off.					
	UNUSUAL	Red; Indicating the machine is executing protection, when protection finished, goes off.					
Environmental	Operating temperature	0~40℃					
	Storage Temperature	-15℃~45℃					
	Operating Relative Humidity	10% RH~102%RH; Non-condensing					
Physical	Machine Size(mm)	227×110×152	240×140×188	240×140×188	240×140×188	352×220×256	352×220×256
	N.W.(Kgs)	2.5	4.8	5.5	6.3	12.55	15.5