

SDR 系列数码显示豪华型电子式稳压器
DIGITAL FACE WITH POWERFUL HEART
SDR SERIES/RELAY TYPE



SDR-1000VA



SDR-1500VA



SDR-2000VA



SDR-3000VA



SDR-5000VA

| Model | | SDR-1000VA | SDR-1500VA | SDR-2000VA | SDR-3000VA | SDR-5000VA |
|----------------------------|-----------------------------|---|-------------|-------------|-------------|-------------|
| Power | | 1000VA | 1500VA | 2000VA | 3000VA | 5000VA |
| Input | Input voltage Range | 140-260VAC | | | | |
| | Input Frequency | 50/60Hz | | | | |
| Output | Output voltage | 220 VAC | | | | |
| | Output Precision | ± 8% | | | | |
| Efficiency | | 98% | | | | |
| Phase | | Single Phase | | | | |
| Digital LED display status | | Input voltage / Output voltage | | | | |
| LED display status | WORKING | Red; Indicating power ON/OFF. | | | | |
| | INPUT | Yellow; During display input voltage, this LED keep lighting, display output voltage, goes off. | | | | |
| | OUTPUT | Red; During display output voltage, this LED keep lighting, display input voltage, goes off. | | | | |
| Environmental | Operating temperature | 0~40℃ | | | | |
| | Storage temperature | -15℃~45℃ | | | | |
| | Operating Relative Humidity | 10% RH~102%RH; Non-condensing | | | | |
| Physical | Machine Size(mm) | 295×140×188 | 295×140×188 | 295×140×188 | 352×220×256 | 352×220×256 |
| | N.W.(Kgs) | 4.75 | 5.35 | 6.25 | 12.2 | 15.3 |